图纸履历 PLAN HISTORY							
日期 DATE	标记 MARKER	数量 NUMBER	版本 REV.	修改单号/说明 MODIFICATION NO./DESCRIPTION	页码 PAGE	设计 Designed	审核 Reviewed

NOTES:

1. THE SMALL HATCH COVERS MUST MEET THE SOLAS&GL RULES.
2. THE SMALL HATCH COVERS (ITEM 1 , 3 AND 12) MUST FOLLOW THE REQUIREMENTS OF IACS URS26.
3. THE WELDING LEG BETWEEN HATCH COAMING AND DECK IS K=8/8.
4. THE DIMENSION WITH MARK * IS PRELIMINARY, WHICH MAY BE ADJUSTED ACCORDING TO THE APPROVED DRAWING OF THE LASHING BRIDGE AND CARGO HATCH COVER.
5. THE HATCHES (ITEM 1) USED FOR ROPE HANDLING ALSO SHOULD HAVE PROTECTOR STEEL ROUND BAR FOR RUNNING OF ROPE WHERE SHARP EDGE EXISTS AT COAMING OR DECK BEAM ETC. AND TO BE FITTED WITH ROLLERS IF NECESSARY.
6. THE CONSTITUTION OF HATCH COVERS SHOWN IN THE DRAWING IS FOR REFERENCE ONLY, WHICH WILL BE SHOWN IN THE DRAWING OFFERED BY THE HATCH MAKER.

注：

1. 小舱口盖必须满足SOLAS及GL有关规定.
2. 小舱盖(件号1, 3和12)必须满足IACS URS26 的要求.
3. 小舱口围板与船体甲板焊脚为: K=8/8.
4. 本图带*号的尺寸是初步的,可能要按绑扎桥和舱盖的认可图调整.
5. 小舱盖(件号1)兼缆索舱口盖,所以缆索经过的小舱口围或甲板梁等如有尖角, 要用圆钢保护, 如有必要加滚轮.
6. 本图所表示关于小舱口盖的构造细节仅供参考,具体参见小舱口盖厂商的图纸.
7. 本图材料表的所有零件均为外购。
8. 小舱口盖围槛安装高度不小于600mm。

ITEM NO. 序号	MARK 代号	NAME & SPEC 名称及规格	QTY. 数量	SURFACE-INSIDE OPENING 甲板开口尺寸	WEIGHT(KG) 重量(kg) SIN. 每件	WEIGHT(KG) 重量(kg) TOT. 单件	REMARKS 附注
15		防护材 t=10mm PROTECTION	3				
14		U 型眼环 ø16 U TYPE RING	2		0.02	0.04	
13	630X630X8-12X450 仿 CB/T 3728-1995	弹簧铰链快开闭风雨密舱口盖 SPRING HINGED WEATHER TIGHT HATCH COVER	1	600X600 R100	146	146	风雨密 WEATHER TIGHT
12	A630X630X8-11X680 REFER TO 仿 CB/T 3728-1995	钢质风雨密小舱口盖 WEATHERTIGHT SMALL HATCH COVER	2	600X600 R100	225	450	SATISFIED WITH 需满足 IACS URS26 的要求
11	B630X630X8-8X150 CB/T 3728-1995	钢质风雨密小舱口盖 WEATHERTIGHT SMALL HATCH COVER	1	600X600 R100		75	
10	ø556-H600/H1600 CBM2013-81 263WHL017-00	缆索舱舱口盖 ROPE HANDLING HATCH COVER	1	ø522		120.5	
9	2380X2180X14 263WHL006-00	机舱备件小舱口盖 SMALL HATCH COVER FOR ENGINE SPARES	1	2200X2000 R100		~1222	
8	B 770X770X12-12X200 263WHL005-00	通向管弄耐压小舱盖 PRESSURE HATCH COVER TO PIPE TUNNEL	1	740X740 R100		340	压力≥0.2 MPa PRESSURE
7	A1030X1030X8-11X600 CB/T 3728-1995	钢质风雨密小舱口盖 WEATHERTIGHT SMALL HATCH COVER	1	1000X1000 R100	404	404	
6	B 1230X1230X8-11X600 CB/T 3728-1995	钢质风雨密小舱口盖 WEATHERTIGHT SMALL HATCH COVER	2	1200X1200 R100	560	1300	
5	B 830X830X8-11X680 CB/T 3728-1995	钢质风雨密小舱口盖 WEATHERTIGHT SMALL HATCH COVER	1	800X800 R100		237	
4	B630X630X8-11X680 CB/T 3728-1995	钢质风雨密小舱口盖 WEATHERTIGHT SMALL HATCH COVER	13	600X750 R100	218	2834	
3	A630X630X8-11X680 REFER TO 仿 CB/T 3728-1995	钢质风雨密小舱口盖 WEATHERTIGHT SMALL HATCH COVER	5	600X750 R100	225	1125	SATISFIED WITH 需满足 IACS URS26 的要求
2		防磨圆钢 ROUND BAR ø16	1			7.3	MATERIAL 材料为 SUS304
1	A1230X1230X8-11X600 REFER TO 仿 CB* 3200-1984	苏伊士运河灯舱口盖 HATCH COVER FOR SUEZ CANAL LIGHT	1	1200X1200 R100		650	SATISFIED WITH 需满足 IACS URS26 的要求

JNSD
Shanghai China
Tel: +86-021-53025656
Fax: +86-021-63012364
E-mail:jnsd@jnshipyard.com.cn

5,100箱集装箱船 5,100TEU CONTAINER VESSEL		设计阶段 DES.STA.	完工设计 FINISH DESIGN		
		工程号 HULL NO.	H2431		
文件号 FILE		版本 REV.		全船小舱口盖与人空盖布置图 ARRANGEMENT OF SMALL HATCH COVER AND MANHOLE	图号 DRAWING NO. FO-15-01 72001500D-01
设绘 DESIGNED		审核 EXAMINE			重量(kg) WEIGHT 8911; 比例 SCALE 1:250; 面积m² AREA
校对 CHECKED		复审 REVIEWED		全船小舱口盖布置图 ARRANGEMENT OF SMALL HATCH COVER	共 1 页 TOTAL SHEETS; 第 1 页 SHEET
会签 COUNTERSIGN		审定 APPROVED			上海江南长兴重工有限责任公司 SHANGHAI JIANGNAN CHANGXING HEAVY INDUSTRY CO.,LTD.
标检 STANDARDIZED		批准 AGREED			

总面积: 594X1471=0.88m²