

**Indian Maritime University**  
**(A Central University, Govt of India)**

**Supplementary Examinations – September/October 2024**

**Programme Name: B. Tech. (Marine Engineering)**

**Semester: 5<sup>th</sup> Semester**

**Subject Code: UG11T4509**

**Subject Name: HEAT TRANSFER AND MARINE HEAT EXCHANGERS**

Date: 23.10.2024	Max Marks: 70
Duration: 03 Hrs	Pass Marks: 35

General Instructions

- (i) All Sections (A, B & C) are to be attempted.
- (ii) Options, if any, are specified in respective section.
- (iii) Heat Transfer Data Handbook can be used.

**Section A**

Ten MCQs/Fill in the Blanks of 01 Mark each – Choose the correct answer as applicable.

1. Thermal contact resistance is a function of
  - a) surface roughness
  - b) the pressure holding the two surfaces in contact
  - c) the interface fluid and its temperature
  - d) all of the above
  
2. The relationship  $(\text{Wavelength})_{\max} T = \text{constant}$ , between the temperature of a black body and the wavelength at which maximum value of monochromatic emissive power occurs is known as
  - a) Planck's law
  - b) Kirchoff's law
  - c) Lambert's law
  - d) Wein's law
  
3. A composite wall consists of two layers of same surface area (in the direction of the heat flow) of different materials having conductivities  $k_1$  and  $k_2$ . If thickness of layer 1 is twice the thickness of layer 2, then the equivalent thermal conductivity of the slab will be
  - a)  $k_1 + k_2$
  - b)  $k_1 k_2$

c)  $\frac{2k_1k_2}{k_1+k_2}$

d)  $\frac{3k_1k_2}{k_1+2k_2}$

4. What does NTU indicate?
- Effectiveness of heat exchanger
  - Efficiency of heat exchanger
  - Size of heat exchanger
  - Temperature drop in heat exchanger
5. For the fully developed laminar flow and heat transfer in a uniformly heated long circular tube, if the flow velocity is doubled and the tube diameter is halved, the heat transfer coefficient will be
- Double of the original value
  - Half of the original value
  - Same as before
  - Four times of the original value
6. Gases have poor
- transmissivity
  - absorptivity
  - reflectivity
  - emissivity
7. Which non-dimensional number relates the thermal boundary layer and hydrodynamic boundary layer?
- Prandtl Number
  - Grashof Number
  - Peclet Number
  - Reynold Number
8. For calculation of heat transfer by natural convection from a horizontal cylinder, what is the characteristic length in Grashof number?
- Diameter of the cylinder
  - Length of the cylinder
  - Circumference of the base of the cylinder
  - Half the circumference of the base of the cylinder
9. Forced convection dominates if
- $Gr/Re^2 \ll 1$
  - $Gr/Re^2 \gg 1$
  - $Gr/Re^2 = 1$
  - $Gr.Pr/Re^2 \gg 1$
10. Emissivity of a surface depends on
- Temperature
  - Roughness
  - View factor

- d) Both (a) and (b)

### **Section B**

Five Questions of 02 Marks each

11. What will happen to the heat transfer rate if we increase the thickness of insulation above the critical radius of insulation?
12. How does fins / extended surfaces aids in the heat transfer?
13. Define Reynold's Number and Grashoff's Number.
14. Differentiate the parallel flow and counterflow heat exchangers.
15. State the Kirchhoff's law of heat radiation?

### **Section C**

Seven Questions of 10 Marks each of which any 05 questions to be answered.

16. Dry saturated steam at 10 bar enters a counter-flow heat exchanger at the rate of 15 kg/s and leaves at 280 °C. The entry of gas at 600 °C is with mass flow rate of 25 kg/s. If the condenser tubes are 35 mm diameter and 4 m long, make calculations for the heating surface area and the number of tubes required. Neglect the resistance offered by the metallic tubes. Take the following properties for steam and gas:

For steam:  $t_{sat} = 180\text{ }^{\circ}\text{C}$ (at 10 bar),  $C_{ps} = 2.7\text{ kJ/kg-K}$  &  $h_s = 600\text{ W/m}^2\text{-}^{\circ}\text{C}$

For gas:  $C_{pg} = 1\text{ kJ/kg-K}$  &  $h_g = 250\text{ W/m}^2\text{-}^{\circ}\text{C}$ .

**(10 marks)**

17. Derive the general 1-Dimensional steady state heat conduction equation in cartesian coordinate system.

**(10 marks)**

18. Draw the TEMA standard heat exchanger with channel and removable cover and one object pass (AES) and mention the various parts. **(10 Marks)**

19. A steam main 80 mm inside diameter and 90 mm outside diameter is lagged with two successive layers of insulation. The layer in contact with the pipe is 40 mm asbestos and the asbestos layer is covered with 25 mm thick magnesia insulation. The surface coefficients for inside and outside surfaces are 227 W/m<sup>2</sup>-K and 6.8 W/m<sup>2</sup>-K respectively. If the steam temperature is 400 °C and the ambient temperature is 30 °C, calculate
- a) the steady state loss of heat from steam for 60 m length of pipe.

- b) the overall coefficient of heat transfer based on the inside and outside surfaces of the lagged steam main.

Thermal conductivity values of the pipe material, asbestos and magnesia insulation are 45 W/m-K, 0.14 W/m-K & 0.07 W/m-K respectively.

**(7 + 3 marks)**

20. A steel rod ( $k = 30$  W/m-deg) 10 mm in diameter and 50 mm long protrudes from a wall which is maintained at  $100^\circ\text{C}$ . The rod is insulated at its tip and is exposed to an environment with  $h = 50$  W/m<sup>2</sup>-deg and  $t_a = 30^\circ\text{C}$ . Estimate the following:
- fin efficiency
  - temperature at the tip of fin
  - rate of heat dissipation

**(4 + 3 + 3 marks)**

21. A counter-flow double-pipe heat exchanger is to heat water from  $20^\circ\text{C}$  to  $80^\circ\text{C}$  at a rate of 1.2 kg/s. The heating is to be accomplished by geothermal water available at  $160^\circ\text{C}$  at a mass flow rate of 2 kg/s. The inner tube is thin-walled and has a diameter of 1.5 cm. If the overall heat transfer coefficient of the heat exchanger is 640 W/m<sup>2</sup>.K, using the NTU-method determine the length of the heat exchanger required to achieve the desired heating. ( $C_p$  of water = 4.18 kJ/kg.K;  $C_p$  of geothermal water = 4.31 kJ/kg.K)

**(10 marks)**

22. a) Explain briefly the extended surfaces or fins **(4 Marks)**  
b) Derive an expression for LMTD in Parallel Flow Heat Exchangers. **(6 Marks)**